

- **Materiál patka:** galvanizovaná ocel + vulkanizovaná guma NBR 80 Shore
- **Materiál šroub:** galvanizovaná ocel C40
- **Barva patky:** stříbrná + černá

Zmíněné statické zatížení je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

Selected variant

| | |
|-----------------------------|---|
| Product name | Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel |
| Product code | 14462 |
| SW key | 20 |
| Height A (mm) | 36 |
| Foot height G (mm) | 25 |
| Pitch I (mm) | 54 |
| Foot diameter D (mm) | 80 |
| Static load (N) | 10000 |
| Screw length B (mm) | 100 |
| Height H (mm) | 136 |
| Thread F | M20 |

Variants

| Product name | Product code | QTY | SW key | Height A (mm) | Foot height G (mm) | Pitch I (mm) | Foot diameter D (mm) | Static load (N) | Screw length B (mm) | Height H (mm) | Thread F |
|---|--------------|-----|--------|---------------|--------------------|--------------|----------------------|-----------------|---------------------|---------------|----------|
| Adjustable leg with vulcanized foot ø80 mm and eyelet, galvanized steel | 14449 | 11 | 14 | 35 | 25 | 54 | 80 | 10000 | 50 | 85 | M10 |

| Product name | Product code | QTY | SW key | Height A (mm) | Foot height G (mm) | Pitch I (mm) | Foot diameter D (mm) | Static load (N) | Screw length B (mm) | Height H (mm) | Thread F |
|---|--------------|-----|--------|---------------|--------------------|--------------|----------------------|-----------------|---------------------|---------------|----------|
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel | 14450 | 13 | 14 | 35 | 25 | 54 | 80 | 10000 | 100 | 135 | M10 |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel | 14451 | 0 | 14 | 35 | 25 | 54 | 80 | 10000 | 50 | 85 | M12 |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel | 14452 | 4 | 14 | 35 | 25 | 54 | 80 | 10000 | 100 | 135 | M12 |
| Pipe covers Type 1, LDPE, natural, yellow, black, red, white | 14453 | 2 | 14 | 35 | 25 | 54 | 80 | 10000 | 150 | 185 | M12 |
| Adjustable foot with vulcan. with foot ø80 mm and eyelet, galvanized. steel | 14454 | 0 | 14 | 35 | 25 | 54 | 80 | 10000 | 50 | 85 | M14 |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel | 14455 | 0 | 14 | 35 | 25 | 54 | 80 | 10000 | 100 | 135 | M14 |

| Product name | Product code | QTY | SW key | Height A (mm) | Foot height G (mm) | Pitch I (mm) | Foot diameter D (mm) | Static load (N) | Screw length B (mm) | Height H (mm) | Thread F |
|--|--------------|-----|--------|---------------|--------------------|--------------|----------------------|-----------------|---------------------|---------------|----------|
| Adjustable foot with vulcan. foot ø80 mm and eyelet, galvanised steel | 14456 | 0 | 14 | 35 | 25 | 54 | 80 | 10000 | 150 | 185 | M14 |
| Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel | 14457 | 5 | 14 | 35 | 25 | 54 | 80 | 10000 | 50 | 85 | M16 |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanised steel | 14458 | 13 | 14 | 35 | 25 | 54 | 80 | 10000 | 100 | 135 | M16 |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel | 14459 | 6 | 14 | 35 | 25 | 54 | 80 | 10000 | 150 | 185 | M16 |
| Adjustable foot with vulcan. with foot ø80 mm and eye, galvanized steel | 14460 | 2 | 14 | 35 | 25 | 54 | 80 | 10000 | 200 | 235 | M16 |
| Adjustable foot with vulcanized foot ø80 mm and eyelet, galvanized steel | 14461 | 5 | 20 | 36 | 25 | 54 | 80 | 10000 | 75 | 111 | M20 |

| Product name | Product code | QTY | SW key | Height A (mm) | Foot height G (mm) | Pitch I (mm) | Foot diameter D (mm) | Static load (N) | Screw length B (mm) | Height H (mm) | Thread F |
|---|--------------|-----|--------|---------------|--------------------|--------------|----------------------|-----------------|---------------------|---------------|----------|
| Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel | 14462 | 0 | 20 | 36 | 25 | 54 | 80 | 10000 | 100 | 136 | M20 |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel | 14463 | 0 | 20 | 36 | 25 | 54 | 80 | 10000 | 150 | 186 | M20 |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel | 14464 | 0 | 20 | 36 | 25 | 54 | 80 | 10000 | 200 | 236 | M20 |
| Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel | 14465 | 0 | 24 | 36 | 25 | 54 | 80 | 10000 | 75 | 111 | M24 |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel | 14466 | 10 | 24 | 36 | 25 | 54 | 80 | 10000 | 100 | 136 | M24 |
| Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel | 14467 | 0 | 24 | 36 | 25 | 54 | 80 | 10000 | 150 | 186 | M24 |

| Product name | Product code | QTY | SW key | Height A (mm) | Foot height G (mm) | Pitch I (mm) | Foot diameter D (mm) | Static load (N) | Screw length B (mm) | Height H (mm) | Thread F |
|---|--------------|-----|--------|---------------|--------------------|--------------|----------------------|-----------------|---------------------|---------------|----------|
| Adjustable leg with vulcanized foot ø80 mm and eye, galvanized. steel | 14468 | 5 | 24 | 36 | 25 | 54 | 80 | 10000 | 200 | 236 | M24 |

A components s.r.o.Bohunická 493/81
619 00 BrnoWeb: www.acomponents.czE-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.