

- **Material:** polyamide 6.6 with an additive that increases the material's resistance to UV radiation
- **Color:** black
- **Operating temperature:** -40°C to +85°C
- **Flammability of the material:** complies with UL 94V-2

Packed in packs of 100.

Certified according to UL 62275 type 2.21 and IEC 62275 type 2; including UV.

Selected variant

Product name	UV-resistant cable ties, black
Product code	0
width	7,5
Min. tensile strength (kg)	46
Maximum closing diameter (mm)	101
Color	černá
Length L (mm)	360

Variants

Product name	Product code	QTY	width	Min. tensile strength (kg)	Maximum closing diameter (mm)	Color	Length L (mm)
UV-resistant cable ties, black	30887	0	4,5	22	76	černá	280
0	31074	0	3,5	15	36	černá	140
UV-resistant cable ties, black	31076	0	4,5	22	101	černá	360
UV-resistant cable ties, black	31075	0	4,5	22	51	černá	200
UV-resistant cable ties, black	31078	0	7,5	46	160	černá	540
UV-resistant cable ties, black	31079	0	7,5	68	235	černá	750

Product name	Product code	QTY	width	Min. tensile strength (kg)	Maximum closing diameter (mm)	Color	Length L (mm)
UV-resistant cable ties, black	31077	0	7,5	46	101	černá	360

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.czE-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.