

- **Materiál patka:** Termoplast se skleněnými vlákny
- **Materiál šroub:** Pozinkovaná ocel
- **Barva patky:** Černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

Selected variant

Product name	Adjustable foot with foot ø50 mm, PA+GF-steel
Product code	13749
Thread F	M12
Foot diameter D (mm)	50
Foot height G (mm)	20
Height with washer H1 (mm)	158
Screw length B (mm)	125
Height without washer H (mm)	155
Height A (mm)	30
Static load (N)	11000
SW key	14

Variants

Product name	Product code	QTY	Thread F	Foot diameter D (mm)	Foot height G (mm)	Height with washer H1 (mm)	Screw length B (mm)	Height without washer H (mm)	Height A (mm)	Static load (N)	SW key
Adjustable foot with foot ø50 mm, PA+GF-steel	13752	10	M14	50	20	108	75	105	30	11000	14

Product name	Product code	QTY	Thread F	Foot diameter D (mm)	Foot height G (mm)	Height with washer H1 (mm)	Screw length B (mm)	Height without washer H (mm)	Height A (mm)	Static load (N)	SW key
Adjustable foot with foot ø50 mm, PA+GF-steel	13740	0	M10	50	20	58	25	55	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13741	10	M10	50	20	83	50	80	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13742	10	M10	50	20	108	75	105	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13743	10	M10	50	20	166	100	130	30	11000	14
Adjustable foot with foot ø50 mm, PA + GF-steel	13744	10	M10	50	20	158	125	155	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13745	10	M12	50	20	58	25	55	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13746	10	M12	50	20	83	50	80	30	11000	14

Product name	Product code	QTY	Thread F	Foot diameter D (mm)	Foot height G (mm)	Height with washer H1 (mm)	Screw length B (mm)	Height without washer H (mm)	Height A (mm)	Static load (N)	SW key
Adjustable foot with foot ø50 mm, PA+GF-steel	13747	10	M12	50	20	108	75	105	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13748	5	M12	50	20	166	100	130	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13749	10	M12	50	20	158	125	155	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13751	10	M14	50	20	83	50	80	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13753	10	M14	50	20	166	100	130	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13754	10	M14	50	20	158	125	155	30	11000	14