

- **Foot material:** galvanized steel + vulcanized rubber NBR 80 Shore
- **Screw material:** galvanized steel C40
- **Foot color:** silver + black

The static load mentioned is calculated at the center of the screw. In case of vibrations or dynamic loads, these values are lower.

## Selected variant

<b>Product name</b>	Adjustable foot with vulcan. foot ø50 mm, galvanized steel
<b>Product code</b>	14312
<b>Screw length B (mm)</b>	150
<b>Foot diameter D (mm)</b>	50
<b>Height H (mm)</b>	179
<b>Thread F</b>	M16
<b>SW key</b>	16
<b>Foot height G (mm)</b>	19
<b>Static load (N)</b>	4000
<b>Height A (mm)</b>	29

## Variants

Product name	Product code	QTY	Screw length B (mm)	Foot diameter D (mm)	Height H (mm)	Thread F	SW key	Foot height G (mm)	Static load (N)	Height A (mm)
Adjustable foot with vulcan. foot ø50 mm, galvanized steel	14302	10	50	50	79	M10	14	19	4000	29
Adjustable foot with vulcan. foot ø50 mm, galvanized steel	14303	10	100	50	129	M10	14	19	4000	29

Product name	Product code	QTY	Screw length B (mm)	Foot diameter D (mm)	Height H (mm)	Thread F	SW key	Foot height G (mm)	Static load (N)	Height A (mm)
Adjustable foot with vulcanized foot ø50 mm, galvanized steel	14304	0	50	50	79	M12	14	19	4000	29
Adjustable foot with vulcan. foot ø50 mm, galvanized steel	14305	4	100	50	129	M12	14	19	4000	29
Adjustable foot with vulcan. foot ø50 mm, galvanized steel	14306	2	150	50	179	M12	14	19	4000	29
Adjustable foot with vulcan. foot ø50 mm, galvanized. steel	14307	0	50	50	79	M14	14	19	4000	29
Adjustable foot with vulcanized foot ø50 mm, galvanized steel	14308	0	100	50	129	M14	14	19	4000	29
Adjustable foot with vulcan. foot ø50 mm, galvanized. steel	14309	0	150	50	179	M14	14	19	4000	29
Adjustable foot with vulcanized foot ø50 mm, galvanized steel	14310	5	75	50	104	M16	16	19	4000	29
Adjustable foot with vulcan. foot ø50 mm, galvanized steel	14311	10	100	50	129	M16	16	19	4000	29
Adjustable foot with vulcan. foot ø50 mm, galvanized steel	14312	6	150	50	179	M16	16	19	4000	29

Product name	Product code	QTY	Screw length B (mm)	Foot diameter D (mm)	Height H (mm)	Thread F	SW key	Foot height G (mm)	Static load (N)	Height A (mm)
Adjustable foot with vulcanized foot ø50 mm, galvanized steel	14313	2	200	50	229	M16	16	19	4000	29

**A components s.r.o.**

Bohunická 493/81  
619 00 Brno

Web: [www.acomponents.cz](http://www.acomponents.cz)  
E-mail: [info@acomponents.cz](mailto:info@acomponents.cz)  
Telefon: 511 188 963

**Maloobchodní prodej**

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.