

USIT ring with centering lip USS is a top-notch sealing element designed for maximum reliability and durability. This special ring combines the advantages of a traditional USIT ring with the addition of a vulcanized centering lip, which ensures precise positioning and minimizes the risk of leakage.

When tightening the fitting (connection), the sealing lip rests on the opposing surfaces, which are thus sealed by it. Made of high-quality materials, it is resistant to high pressures and temperatures, which makes it ideal for demanding industrial applications. Thanks to its design, it is easy to install and provides long-term wear protection.

- **Material:** steel/NBR

Zvolená varianta

Název produktu	USIT kroužek 22.70 x 30.00 x 2.00 mm, M22, NBR, s centrovacím břítem, USS
Kód	0
Materiál	ocel / NBR
Závit	M22
t.	2
d.	22,7
Průměr D (mm)	30

Varianty produktu

Název produktu	Kód	QTY	Materiál	Závit	t.	d.	Průměr D (mm)
USIT kroužek 13.74 x 20.57 x 2.03 mm, 1/4", NBR, s centrovacím břítem, USS	30551	7869	ocel / NBR	1/4"	2,03	13,74	20,57
USIT kroužek 8.70 x 13.00 x 1.00 mm, M8, NBR, s centrovacím břítem, USS	30562	1200	ocel / NBR	M8	1	8,7	13
USIT kroužek 24.70 x 32.00 x 2.00 mm, M24, NBR, s centrovacím břítem, USS	30564	1350	ocel / NBR	M24	2	24,7	32
USIT kroužek 20.70 x 28.00 x 1.50 mm, M20, NBR, s centrovacím břítem, USS	30563	1194	ocel / NBR	M20	1,5	20,7	28
USIT kroužek 60.58 x 73.03 x 3.20 mm, 2", NBR, s centrovacím břítem, USS	30568	613	ocel / NBR	2"	3,2	60,58	73,03
USIT kroužek 33.89 x 42.80 x 2.50 mm, 1", NBR, s centrovacím břítem, USS	30554	2070	ocel / NBR	1"	2,5	33,89	42,8

Název produktu	Kód	QTY	Materiál	Závit	t.	d.	Průměr D (mm)
USIT kroužek 16.70 x 24.00 x 1.50 mm, M16, NBR, s centrovacím břítem, USS	30555	1755	ocel / NBR	M16	1,5	16,7	24
USIT kroužek 27.05 x 34.93 x 2.50 mm, 3/4", NBR, s centrovacím břítem, USS	30552	6229	ocel / NBR	3/4"	2,5	27,05	34,93
USIT kroužek 42.93 x 52.38 x 2.50 mm, 1 1/4", NBR, s centrovacím břítem, USS	30561	895	ocel / NBR	1 1/4"	2,5	42,93	52,38
USIT kroužek 23.49 x 31.75 x 2.50 mm, 5/8", NBR, s centrovacím břítem, USS	30569	578	ocel / NBR	5/8"	2,5	23,49	31,75
USIT kroužek 17.28 x 23.80 x 2.03 mm, 3/8", NBR, s centrovacím břítem, USS	30549	4400	ocel / NBR	3/8"	2,03	17,28	23,8
USIT kroužek 21.54 x 28.58 x 2.50 mm, 1/2", NBR, s centrovacím břítem, USS	30550	4130	ocel / NBR	1/2"	2,5	21,54	28,58
USIT kroužek 22.70 x 30.00 x 2.00 mm, M22, NBR, s centrovacím břítem, USS	30557	1950	ocel / NBR	M22	2	22,7	30
USIT kroužek 18.70 x 26.00 x 1.50 mm, M18, NBR, s centrovacím břítem, USS	30558	1020	ocel / NBR	M18	1,5	18,7	26
USIT kroužek 26.70 x 35.00 x 2.00 mm, M26, NBR, s centrovacím břítem, USS	30565	1059	ocel / NBR	M26	2	26,7	35
USIT kroužek 48.44 x 58.60 x 2.50 mm, 1 1/2", NBR, s centrovacím břítem, USS	30567	585	ocel / NBR	1 1/2"	2,5	48,44	58,6
USIT kroužek 10.37 x 15.88 x 2.03 mm, 1/8", NBR, s centrovacím břítem, USS	30553	3335	ocel / NBR	1/8"	2,03	10,37	15,88
USIT kroužek 14.70 x 22.00 x 1.50 mm, M14, NBR, s centrovacím břítem, USS	30556	4330	ocel / NBR	M14	1,5	14,7	22
USIT kroužek 10.35 x 15.88 x 2.00 mm, M10, NBR, s centrovacím břítem, USS	30560	1250	ocel / NBR	M10	2,0	10,35	15,88
USIT kroužek 12.70 x 18.00 x 1.50 mm, M12, NBR, s centrovacím břítem, USS	30559	1282	ocel / NBR	M12	1,5	12,7	18
USIT kroužek 6.70 x 10.00 x 1.00 mm, M6, NBR, s centrovacím břítem, USS	30570	409	ocel / NBR	M6	1	6,7	10
USIT kroužek 31.00 x 39.00 x 2.00 mm, M30, NBR, s centrovacím břítem, USS	30566	593	ocel / NBR	M30	2	31	39