

- **Materiál patka:** Termoplast se skleněnými vlákny
- **Materiál šroub:** Pozinkovaná ocel
- **Barva patky:** Černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

## Selected variant

<b>Product name</b>	Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel
<b>Product code</b>	14400
<b>Foot height G (mm)</b>	32
<b>Pitch K (mm)</b>	73
<b>Static load (N)</b>	25000
<b>Thread F</b>	M20
<b>SW key</b>	20
<b>Foot diameter D (mm)</b>	103
<b>Height without washer H (mm)</b>	201
<b>Screw length B (mm)</b>	150
<b>Height with washer H1 (mm)</b>	204
<b>Height A (mm)</b>	51
<b>Hole diameter L (mm)</b>	12,5

## Variants

Product name	Product code	QTY	Foot height G (mm)	Pitch K (mm)	Static load (N)	Thread F	SW key	Foot diameter D (mm)	Height without washer H (mm)	Screw length B (mm)	Height with washer H1 (mm)	Height A (mm)	Hole diameter L (mm)

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	13915	8	32	73	20000	M16	16	103	101	50	104	51	12,5
Adjustable leg with foot ø103mm and holes for anchoring, PA+GF-steel	13916	8	32	73	20000	M16	16	103	151	100	154	51	12,5
Adjustable leg with foot ø103mm and holes for anchoring, PA+GF-steel	13917	8	32	73	20000	M16	16	103	201	150	204	51	12,5
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	13918	8	32	73	20000	M16	16	103	251	200	254	51	12,5
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14397	8	32	73	25000	M20	20	103	126	75	129	51	12,5

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14398	8	32	73	25000	M20	20	103	151	100	154	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14399	8	32	73	25000	M20	20	103	176	125	179	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14400	8	32	73	25000	M20	20	103	201	150	204	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14401	0	32	73	25000	M20	20	103	226	175	229	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14402	0	32	73	25000	M20	20	103	251	200	254	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------

Adjustable foot with foot $\varnothing$ 103mm and holes for anchoring, PA+GF- steel	14403	0	32	73	25000	M20	20	103	276	225	279	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------