

- **Materiál patka:** Termoplast se skleněnými vlákny
- **Materiál šroub:** Pozinkovaná ocel
- **Barva patky:** Černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

Selected variant

Product name	Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel
Product code	13939
Thread F	M16
SW key	13
Foot height G (mm)	32
Height without washer H (mm)	247
Screw length B (mm)	200
Foot diameter D (mm)	103
Height with washer H1 (mm)	250
Pitch K (mm)	73
Hole diameter L (mm)	12,5
Static load (N)	20000
Height A (mm)	47

Variants

Product name	Product code	QTY	Thread F	SW key	Foot height G (mm)	Height without washer H (mm)	Screw length B (mm)	Foot diameter D (mm)	Height with washer H1 (mm)	Pitch K (mm)	Hole diameter L (mm)	Static load (N)	Height A (mm)
--------------	--------------	-----	----------	--------	--------------------	------------------------------	---------------------	----------------------	----------------------------	--------------	----------------------	-----------------	---------------

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	13936	8	M16	13	32	97	50	103	100	73	12,5	20000	47
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	13937	8	M16	13	32	147	100	103	150	73	12,5	20000	47
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	13938	8	M16	13	32	197	150	103	200	73	12,5	20000	47
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	13939	2	M16	13	32	247	200	103	250	73	12,5	20000	47

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	14248	8	M20	20	32	176	125	103	179	73	12,5	25000	51
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	14418	8	M20	20	32	126	75	103	129	73	12,5	25000	51
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	14419	8	M20	20	32	151	100	103	154	73	12,5	25000	51
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	14420	8	M20	20	32	201	150	103	204	73	12,5	25000	51

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	14421	0	M20	20	32	226	175	103	229	73	12,5	25000	51
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	14422	0	M20	20	32	251	200	103	254	73	12,5	25000	51
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel	14423	0	M20	20	32	276	225	103	279	73	12,5	25000	51