

The perforated hose clamp has a thread formed by holes in the strip.

A clamp with a strip width of 12 mm has a destructive tightening torque of up to 15 Nm, which is approximately 3 times more than classic W1 hose clamps, which have a thread pressed into the strip.

The more durable the hose, the greater the tightening torque we can use.

Soft hoses cause the buckle to jump when tightened - the strap bends into the pliable material.

The clamping ranges of the buckle are from 6 to 76 mm in diameter.

For larger clamping ranges, an endless strap is designed.

- **Material:** stainless chrome-nickel steel

Zvolená varianta

Název produktu	Hadicová spona perforovaná, W4, 40-63
Kód	0
Šířka (mm)	12
Průměr (mm)	40-63

Varianty produktu

Název produktu	Kód	QTY	Šířka (mm)	Průměr (mm)
Hadicová spona perforovaná, W4, 6-16	00199	1	8	6-16
Hadicová spona perforovaná, W4, 11-20	00200	8	8	11-20
Hadicová spona perforovaná, W4, 13-25	00201	0	8	13-25
Hadicová spona perforovaná, W4, 21-38	00203	36	12	21-38
Hadicová spona perforovaná, W4, 14-27	00202	0	12	14-27
Hadicová spona perforovaná, W4, 27-51	00204	0	12	27-51
Hadicová spona perforovaná, W4, 40-63	00205	0	12	40-63
Hadicová spona perforovaná, W4, 52-76	00206	0	12	52-76