

- **Foot material:** galvanized steel + vulcanized rubber NBR 80 Shore
- **Screw material:** galvanized steel C40
- **Foot color:** silver + black

The static load mentioned is calculated at the center of the screw. In the case of vibrations or dynamic loads, these values are lower.

## Selected variant

|                             |                                                               |
|-----------------------------|---------------------------------------------------------------|
| <b>Product name</b>         | Adjustable foot with vulcanized foot ø80 mm, galvanized steel |
| <b>Product code</b>         | 14353                                                         |
| <b>Height H (mm)</b>        | 236                                                           |
| <b>Foot height G (mm)</b>   | 25                                                            |
| <b>SW key</b>               | 24                                                            |
| <b>Foot diameter D (mm)</b> | 80                                                            |
| <b>Static load (N)</b>      | 10000                                                         |
| <b>Thread F</b>             | M24                                                           |
| <b>Height A (mm)</b>        | 35                                                            |
| <b>Screw length B (mm)</b>  | 200                                                           |

## Variants

| Product name                                                  | Product code | QTY | Height H (mm) | Foot height G (mm) | SW key | Foot diameter D (mm) | Static load (N) | Thread F | Height A (mm) | Screw length B (mm) |
|---------------------------------------------------------------|--------------|-----|---------------|--------------------|--------|----------------------|-----------------|----------|---------------|---------------------|
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel    | 14333        | 1   | 85            | 25                 | 14     | 80                   | 10000           | M10      | 35            | 50                  |
| Adjustable leg with vulcanized foot ø80 mm, galvanized. steel | 14334        | 1   | 135           | 25                 | 14     | 80                   | 10000           | M10      | 35            | 100                 |

| Product name                                                    | Product code | QTY | Height H (mm) | Foot height G (mm) | SW key | Foot diameter D (mm) | Static load (N) | Thread F | Height A (mm) | Screw length B (mm) |
|-----------------------------------------------------------------|--------------|-----|---------------|--------------------|--------|----------------------|-----------------|----------|---------------|---------------------|
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel      | 14335        | 0   | 85            | 25                 | 14     | 80                   | 10000           | M12      | 35            | 50                  |
| Adjustable foot with vulcanized foot ø80mm, galvanized steel    | 14336        | 1   | 135           | 25                 | 14     | 80                   | 10000           | M12      | 35            | 100                 |
| Adjustable leg with vulcanized foot ø80 mm, galvanized steel    | 14337        | 1   | 185           | 25                 | 14     | 80                   | 10000           | M12      | 35            | 150                 |
| Adjustable foot with vulcanized foot ø80 mm, galvanized steel   | 14338        | 0   | 85            | 25                 | 14     | 80                   | 10000           | M14      | 35            | 50                  |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel      | 14339        | 0   | 135           | 25                 | 14     | 80                   | 10000           | M14      | 35            | 100                 |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel      | 14340        | 0   | 185           | 25                 | 14     | 80                   | 10000           | M14      | 35            | 150                 |
| Adjustable leg with vulcanized foot ø80 mm, galvanized. steel   | 14341        | 1   | 110           | 25                 | 14     | 80                   | 10000           | M16      | 35            | 75                  |
| Adjustable leg with vulcan. with foot ø80 mm, galvanized. steel | 14342        | 1   | 135           | 25                 | 16     | 80                   | 10000           | M16      | 35            | 100                 |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel      | 14343        | 1   | 185           | 25                 | 16     | 80                   | 10000           | M16      | 35            | 150                 |

| Product name                                                  | Product code | QTY | Height H (mm) | Foot height G (mm) | SW key | Foot diameter D (mm) | Static load (N) | Thread F | Height A (mm) | Screw length B (mm) |
|---------------------------------------------------------------|--------------|-----|---------------|--------------------|--------|----------------------|-----------------|----------|---------------|---------------------|
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel    | 14344        | 1   | 235           | 25                 | 16     | 80                   | 10000           | M16      | 35            | 200                 |
| Adjustable foot with vulcanized foot ø80 mm, galvanized steel | 14345        | 1   | 111           | 25                 | 20     | 80                   | 10000           | M20      | 35            | 75                  |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel    | 14346        | 0   | 136           | 25                 | 20     | 80                   | 10000           | M20      | 35            | 100                 |
| Adjustable foot with vulcanized foot ø80 mm, galvanized steel | 14347        | 0   | 186           | 25                 | 20     | 80                   | 10000           | M20      | 35            | 150                 |
| Adjustable foot with vulcanized foot ø80 mm, galvanized steel | 14348        | 0   | 236           | 25                 | 20     | 80                   | 10000           | M20      | 35            | 200                 |
| Adjustable leg with vulcan. foot ø80 mm, galvanized steel     | 14349        | 0   | 286           | 25                 | 20     | 80                   | 10000           | M20      | 35            | 250                 |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel    | 14350        | 0   | 111           | 25                 | 24     | 80                   | 10000           | M24      | 35            | 75                  |
| Adjustable leg with vulcanized foot ø80 mm, galvanized steel  | 14351        | 1   | 136           | 25                 | 24     | 80                   | 10000           | M24      | 35            | 100                 |
| Adjustable foot with vulcan. foot ø80 mm, galvanised steel    | 14352        | 0   | 186           | 25                 | 24     | 80                   | 10000           | M24      | 35            | 150                 |

| Product name                                                  | Product code | QTY | Height H (mm) | Foot height G (mm) | SW key | Foot diameter D (mm) | Static load (N) | Thread F | Height A (mm) | Screw length B (mm) |
|---------------------------------------------------------------|--------------|-----|---------------|--------------------|--------|----------------------|-----------------|----------|---------------|---------------------|
| Adjustable foot with vulcanized foot ø80 mm, galvanized steel | 14353        | 1   | 236           | 25                 | 24     | 80                   | 10000           | M24      | 35            | 200                 |

**A components s.r.o.**

Bohunická 493/81

619 00 Brno

 Web: [www.acomponents.cz](http://www.acomponents.cz)

 E-mail: [info@acomponents.cz](mailto:info@acomponents.cz)

Telefon: 511 188 963

**Maloobchodní prodej**

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.