

- **Foot material:** Thermoplastic with glass fibers
- **Screw material:** Galvanized steel
- **Foot color:** Black

The static load, mentioned below in the parameters, is calculated at the center of the screw. These values are reduced in the event of vibrations or dynamic loads.

You can order a [special anti-slip pad](#) for this product.

Selected variant

Product name	Adjustable foot with foot ø50mm, PA+GF-stainless steel
Product code	0
Height without washer H (mm)	130
SW key	14
Foot diameter D (mm)	50
Foot height G (mm)	20
Static load (N)	11000
Screw length B (mm)	100
Height A (mm)	30
Height with washer H1 (mm)	166
Thread F	M14

Variants

Product name	Product code	QTY	Height without washer H (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Screw length B (mm)	Height A (mm)	Height with washer H1 (mm)	Thread F
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13822	2	55	14	50	20	11000	25	30	58	M12

Product name	Product code	QTY	Height without washer H (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Screw length B (mm)	Height A (mm)	Height with washer H1 (mm)	Thread F
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13823	10	80	14	50	20	11000	50	30	83	M12
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13824	10	105	14	50	20	11000	75	30	108	M12
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13825	10	130	14	50	20	11000	100	30	166	M12
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13826	6	155	14	50	20	11000	125	30	158	M12
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13827	6	80	14	50	20	11000	50	30	83	M14

Product name	Product code	QTY	Height without washer H (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Screw length B (mm)	Height A (mm)	Height with washer H1 (mm)	Thread F
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13828	10	105	14	50	20	11000	75	30	108	M14
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13829	10	130	14	50	20	11000	100	30	166	M14
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13830	2	155	14	50	20	11000	125	30	158	M14
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13817	10	55	14	50	20	11000	25	30	58	M10
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13818	9	80	14	50	20	11000	50	30	83	M10

Product name	Product code	QTY	Height without washer H (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Screw length B (mm)	Height A (mm)	Height with washer H1 (mm)	Thread F
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13819	10	105	14	50	20	11000	75	30	108	M10
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13820	10	130	14	50	20	11000	100	30	166	M10
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13821	10	155	14	50	20	11000	125	30	158	M10