

- **Foot material:** Thermoplastic with glass fibers
- **Screw material:** Galvanized steel
- **Foot color:** Black

The static load, mentioned below in the parameters, is calculated at the center of the screw. In case of vibrations or dynamic loads, these values are reduced.

You can order a [special anti-slip pad](#) for this product.

Selected variant

Product name	Adjustable foot with foot ø50 mm, PA+GF-steel
Product code	13746
Thread F	M12
Foot diameter D (mm)	50
Foot height G (mm)	20
Height with washer H1 (mm)	83
Screw length B (mm)	50
Height without washer H (mm)	80
Height A (mm)	30
Static load (N)	11000
SW key	14

Variants

Product name	Product code	QTY	Thread F	Foot diameter D (mm)	Foot height G (mm)	Height with washer H1 (mm)	Screw length B (mm)	Height without washer H (mm)	Height A (mm)	Static load (N)	SW key
Adjustable foot with foot ø50 mm, PA+GF-steel	13752	10	M14	50	20	108	75	105	30	11000	14

Product name	Product code	QTY	Thread F	Foot diameter D (mm)	Foot height G (mm)	Height with washer H1 (mm)	Screw length B (mm)	Height without washer H (mm)	Height A (mm)	Static load (N)	SW key
Adjustable foot with foot ø50 mm, PA+GF-steel	13740	0	M10	50	20	58	25	55	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13741	10	M10	50	20	83	50	80	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13742	10	M10	50	20	108	75	105	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13743	10	M10	50	20	166	100	130	30	11000	14
Adjustable foot with foot ø50 mm, PA + GF-steel	13744	10	M10	50	20	158	125	155	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13745	10	M12	50	20	58	25	55	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13746	10	M12	50	20	83	50	80	30	11000	14

Product name	Product code	QTY	Thread F	Foot diameter D (mm)	Foot height G (mm)	Height with washer H1 (mm)	Screw length B (mm)	Height without washer H (mm)	Height A (mm)	Static load (N)	SW key
Adjustable foot with foot ø50 mm, PA+GF-steel	13747	10	M12	50	20	108	75	105	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13748	5	M12	50	20	166	100	130	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13749	10	M12	50	20	158	125	155	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13751	10	M14	50	20	83	50	80	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13753	10	M14	50	20	166	100	130	30	11000	14
Adjustable foot with foot ø50 mm, PA+GF-steel	13754	10	M14	50	20	158	125	155	30	11000	14