

- **Materiál patka:** galvanizovaná ocel + vulkanizovaná guma NBR 80 Shore
- **Materiál šroub:** galvanizovaná ocel C40
- **Barva patky:** stříbrná + černá

Zmíněné statické zatížení je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

Selected variant

Product name	Adjustable foot with vulcanized foot ø80 mm, galvanized steel
Product code	14348
Height H (mm)	236
Foot height G (mm)	25
SW key	20
Foot diameter D (mm)	80
Static load (N)	10000
Thread F	M20
Height A (mm)	35
Screw length B (mm)	200

Variants

Product name	Product code	QTY	Height H (mm)	Foot height G (mm)	SW key	Foot diameter D (mm)	Static load (N)	Thread F	Height A (mm)	Screw length B (mm)
Adjustable foot with vulcan. foot ø80 mm, galvanized steel	14333	1	85	25	14	80	10000	M10	35	50
Adjustable leg with vulcanized foot ø80 mm, galvanized. steel	14334	1	135	25	14	80	10000	M10	35	100

Product name	Product code	QTY	Height H (mm)	Foot height G (mm)	SW key	Foot diameter D (mm)	Static load (N)	Thread F	Height A (mm)	Screw length B (mm)
Adjustable foot with vulcan. foot ø80 mm, galvanized steel	14335	0	85	25	14	80	10000	M12	35	50
Adjustable foot with vulcanized foot ø80mm, galvanized steel	14336	1	135	25	14	80	10000	M12	35	100
Adjustable leg with vulcanized foot ø80 mm, galvanized steel	14337	1	185	25	14	80	10000	M12	35	150
Adjustable foot with vulcanized foot ø80 mm, galvanized steel	14338	0	85	25	14	80	10000	M14	35	50
Adjustable foot with vulcan. foot ø80 mm, galvanized steel	14339	0	135	25	14	80	10000	M14	35	100
Adjustable foot with vulcan. foot ø80 mm, galvanized steel	14340	0	185	25	14	80	10000	M14	35	150
Adjustable leg with vulcanized foot ø80 mm, galvanized. steel	14341	1	110	25	14	80	10000	M16	35	75
Adjustable leg with vulcan. with foot ø80 mm, galvanized. steel	14342	1	135	25	16	80	10000	M16	35	100
Adjustable foot with vulcan. foot ø80 mm, galvanized steel	14343	1	185	25	16	80	10000	M16	35	150

Product name	Product code	QTY	Height H (mm)	Foot height G (mm)	SW key	Foot diameter D (mm)	Static load (N)	Thread F	Height A (mm)	Screw length B (mm)
Adjustable foot with vulcan. foot ø80 mm, galvanized steel	14344	1	235	25	16	80	10000	M16	35	200
Adjustable foot with vulcanized foot ø80 mm, galvanized steel	14345	1	111	25	20	80	10000	M20	35	75
Adjustable foot with vulcan. foot ø80 mm, galvanized steel	14346	0	136	25	20	80	10000	M20	35	100
Adjustable foot with vulcanized foot ø80 mm, galvanized steel	14347	0	186	25	20	80	10000	M20	35	150
Adjustable foot with vulcanized foot ø80 mm, galvanized steel	14348	0	236	25	20	80	10000	M20	35	200
Adjustable leg with vulcan. foot ø80 mm, galvanized steel	14349	0	286	25	20	80	10000	M20	35	250
Adjustable foot with vulcan. foot ø80 mm, galvanized steel	14350	0	111	25	24	80	10000	M24	35	75
Adjustable leg with vulcanized foot ø80 mm, galvanized steel	14351	1	136	25	24	80	10000	M24	35	100
Adjustable foot with vulcan. foot ø80 mm, galvanized steel	14352	0	186	25	24	80	10000	M24	35	150

Product name	Product code	QTY	Height H (mm)	Foot height G (mm)	SW key	Foot diameter D (mm)	Static load (N)	Thread F	Height A (mm)	Screw length B (mm)
Adjustable foot with vulcanized foot ø80 mm, galvanized steel	14353	1	236	25	24	80	10000	M24	35	200