

SAE flange protection plug designed for 3000 and 6000 PSI. Commonly used to protect products from damage during transportation, heat, dirt, moisture and corrosion.

- **Material:** LDPE
- **Color:** red

Selected variant

Product name	Plugs for connecting SAE flanges, LDPE, red
Product code	0
Height H (mm)	8.7
Height h (mm)	12.3
Diameter d1 (mm)	59.1
PSI	3000
Diameter D (mm)	60.3

Variants

Product name	Product code	QTY	Height H (mm)	Height h (mm)	Diameter d1 (mm)	PSI	Diameter D (mm)
Plugs for connecting SAE flanges, LDPE, red	29897	2	6.7	11.1	29	3000	29.9
Plugs for connecting SAE flanges, LDPE, red	29898	0	8	10.9	37.4	3000	38.1
Caps for connecting SAE flanges, LDPE, red	29903	2	7.8	11.8	31.5	6000	32.2
Plugs for connecting SAE flanges, LDPE, red	29899	0	8	10.5	44	3000	44.7
Plugs for connecting SAE flanges, LDPE, red	29901	0	8.7	12.3	59.1	3000	60.3
Plugs for SAE flanges, LDPE, red	29900	0	8.8	11.9	50.6	3000	51.1
SAE flange connection plugs, LDPE, red	29904	0	8.5	12.2	40.8	6000	41.4

Product name	Product code	QTY	Height H (mm)	Height h (mm)	Diameter d1 (mm)	PSI	Diameter D (mm)
Plugs for connecting SAE flanges, LDPE, red	29905	0	10.2	13.5	46.6	6000	47.7
Plugs for connecting SAE flanges, LDPE, red	29906	0	10.2	13.9	52.7	6000	53.3
Plugs for connecting SAE flanges, LDPE, red	29902	0	9.5	12.7	70.8	3000	70.9
Plugs for connecting SAE flanges, LDPE, red	29907	0	12.5	16.7	62.5	6000	64
SAE flange connection plugs, LDPE, red	29908	0	12.5	15	77.8	6000	79.5