

- **Foot material:** galvanized steel + vulcanized rubber NBR 80 Shore
- **Screw material:** galvanized steel C40
- **Foot color:** silver + black

The mentioned static load is calculated for the center of the screw. These values are reduced in the event of vibrations or dynamic loads.

Selected variant

Product name	Adjustable foot with vulcan. foot ø100mm, galvanized. steel
Product code	14364
SW key	24
Screw length B (mm)	150
Height A (mm)	38,5
Foot diameter D (mm)	100
Foot height G (mm)	28
Static load (N)	15000
Thread F	M24
Height H (mm)	188,5

Variants

Product name	Product code	QTY	SW key	Screw length B (mm)	Height A (mm)	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Thread F	Height H (mm)
Adjustable foot with vulcanized foot ø100mm, galvanized steel	14366	0	24	250	38,5	100	28	15000	M24	288,5
Adjustable leg with vulcanized foot ø100mm, galvanized steel	14354	5	16	75	37,5	100	28	15000	M16	112,5

Product name	Product code	QTY	SW key	Screw length B (mm)	Height A (mm)	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Thread F	Height H (mm)
Adjustable foot with vulcan. foot ø100mm, galvanized steel	14355	71	16	100	37,5	100	28	15000	M16	137,5
Adjustable foot with vulcanized foot ø100mm, galvanized steel	14356	6	16	150	37,5	100	28	15000	M16	187,5
Adjustable foot with vulcanized foot ø100mm, galvanized steel	14357	2	16	200	37,5	100	28	15000	M16	237,5
Adjustable foot with vulcan. foot ø100mm, galvanized steel	14358	5	20	75	38,5	100	28	15000	M20	113,5
Adjustable leg with vulcan. foot ø100mm, galvanized steel	14359	0	20	100	38,5	100	28	15000	M20	138,5
Adjustable foot with vulcan. foot ø100mm, galvanized. steel	14360	0	20	150	38,5	100	28	15000	M20	188,5
Adjustable leg with vulcanized foot ø100mm, galvanized steel	14361	0	20	200	38,5	100	28	15000	M20	238,5
Adjustable foot with vulcan. foot ø100mm, galvanized steel	14362	0	20	250	38,5	100	28	15000	M20	288,5
Adjustable foot with vulcan. foot ø100mm, galvanized steel	14363	10	24	100	38,5	100	28	15000	M24	138,5

Product name	Product code	QTY	SW key	Screw length B (mm)	Height A (mm)	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Thread F	Height H (mm)
Adjustable foot with vulcan. foot ø100mm, galvanized. steel	14364	0	24	150	38,5	100	28	15000	M24	188,5
Adjustable leg with vulcanized foot ø100mm, galvanized steel	14365	5	24	200	38,5	100	28	15000	M24	238,5
Adjustable leg with vulcan. foot Ø100mm, screw M30x100mm, galvanized steel	14367	11	30	100	39,5	100	28	15000	M30	139,5
Adjustable leg with vulcan. foot ø100mm, galvanized steel	14368	0	30	150	39,5	100	28	15000	M30	189,5
Adjustable foot with vulcanized foot ø100mm, galvanized steel	14369	0	30	200	39,5	100	28	15000	M30	239,5
Adjustable foot with vulcan. foot ø100mm, galvanized steel	14370	0	30	250	39,5	100	28	15000	M30	289,5
Adjustable foot with vulcan. foot ø100mm, galvanized steel	28378	4	24	100	30	100	20	35000	M16	133