

The perforated hose clamp has a thread formed by holes in the strip.

The clamp with a strip width of 12 mm has a destructive tightening torque of up to 15 Nm, which is approximately 3 times more than classic W1 hose clamps, which have a thread pressed into the strip.

The more durable the hose, the greater the tightening torque we can use.

Soft hoses cause the clamp to jump when tightened - the strip bends into the pliable material.

The clamping ranges of the clamp are from 6 to 230 mm in diameter.

An endless strip is designed for larger clamping ranges.

- **Material:** galvanized steel

Selected variant

Product name	Perforated clips W1
Product code	0
width	12
Diameter (mm)	130-152

Variants

Product name	Product code	QTY	width	Diameter (mm)
Perforated clips W1	00184	19	8	6-16
Perforované spony W1	00185	0	8	11-20
Perforated clips W1	00187	0	12	14-27
Perforated clips W1	00186	0	8	13-25
Perforated clips W1	00188	8	12	21-38
Perforated clips W1	00189	0	12	27-51
Perforated clips W1	00190	0	12	40-63
Perforated clips W1	00191	0	12	52-76
Perforated clips W1	00193	0	12	84-108
Perforated clips W1	00192	1	12	65-89
Perforated clips W1	00194	17	12	105-127
Perforated clips W1	00195	0	12	130-152

Product name	Product code	QTY	width	Diameter (mm)
Perforated clamps W1	00197	0	12	178-203
Perforated clips W1	00196	0	12	156-178
Perforated clips W1	00198	0	12	203-230