

- **Foot material:** Thermoplastic with glass fibers
- **Screw material:** Galvanized steel
- **Foot color:** Black

The static load, mentioned below in the parameters, is calculated at the center of the screw. In case of vibrations or dynamic loads, these values are reduced.

You can additionally order a [special anti-slip pad](#) for this product.

## Selected variant

|                                     |                                              |
|-------------------------------------|----------------------------------------------|
| <b>Product name</b>                 | Adjustable foot with foot ø40mm, PA+GF-steel |
| <b>Product code</b>                 | 13864                                        |
| <b>Thread F</b>                     | M8                                           |
| <b>Height A (mm)</b>                | 27                                           |
| <b>Height with washer H1 (mm)</b>   | 80                                           |
| <b>Foot diameter D (mm)</b>         | 40                                           |
| <b>SW key</b>                       | 12                                           |
| <b>Screw length B (mm)</b>          | 50                                           |
| <b>Static load (N)</b>              | 10000                                        |
| <b>Foot height G (mm)</b>           | 16,5                                         |
| <b>Height without washer H (mm)</b> | 77                                           |

## Variants

| Product name                                 | Product code | QTY | Thread F | Height A (mm) | Height with washer H1 (mm) | Foot diameter D (mm) | SW key | Screw length B (mm) | Static load (N) | Foot height G (mm) | Height without washer H (mm) |
|----------------------------------------------|--------------|-----|----------|---------------|----------------------------|----------------------|--------|---------------------|-----------------|--------------------|------------------------------|
| Adjustable foot with foot ø40mm, PA+GF-steel | 13863        | 0   | M8       | 27            | 55                         | 40                   | 12     | 25                  | 10000           | 16,5               | 52                           |
| Adjustable foot with foot ø40mm, PA+GF-steel | 13864        | 0   | M8       | 27            | 80                         | 40                   | 12     | 50                  | 10000           | 16,5               | 77                           |

| Product name                                  | Product code | QTY | Thread F | Height A (mm) | Height with washer H1 (mm) | Foot diameter D (mm) | SW key | Screw length B (mm) | Static load (N) | Foot height G (mm) | Height without washer H (mm) |
|-----------------------------------------------|--------------|-----|----------|---------------|----------------------------|----------------------|--------|---------------------|-----------------|--------------------|------------------------------|
| Nastavitelná noha s pátkou ø40mm, PA+GF-ocel' | 13865        | 0   | M8       | 27            | 105                        | 40                   | 12     | 75                  | 10000           | 16,5               | 102                          |
| Adjustable foot with foot ø40mm, PA+GF-steel  | 13866        | 0   | M8       | 27            | 130                        | 40                   | 12     | 100                 | 10000           | 16,5               | 127                          |
| Adjustable foot with foot ø40mm, PA+GF-steel  | 13867        | 0   | M10      | 27            | 55                         | 40                   | 12     | 25                  | 10000           | 16,5               | 52                           |
| Adjustable foot with foot ø40mm, PA+GF-steel  | 13868        | 7   | M10      | 27            | 80                         | 40                   | 12     | 50                  | 10000           | 16,5               | 77                           |
| Adjustable foot with foot ø40mm, PA+GF-steel  | 13869        | 35  | M10      | 27            | 105                        | 40                   | 12     | 75                  | 10000           | 16,5               | 102                          |
| Adjustable foot with foot ø40mm, PA+GF-steel  | 13875        | 1   | M10      | 27            | 130                        | 40                   | 12     | 100                 | 10000           | 16,5               | 127                          |
| Adjustable foot with foot ø40mm, PA+GF-steel  | 13876        | 4   | M10      | 27            | 155                        | 40                   | 12     | 125                 | 10000           | 16,5               | 152                          |
| Adjustable foot with foot ø40 mm, PA+GF-steel | 13877        | 0   | M12      | 27            | 55                         | 40                   | 12     | 25                  | 10000           | 16,5               | 52                           |
| Adjustable foot with foot ø40mm, PA+GF-steel  | 13878        | 1   | M12      | 27            | 80                         | 40                   | 12     | 50                  | 10000           | 16,5               | 77                           |

| Product name                                 | Product code | QTY | Thread F | Height A (mm) | Height with washer H1 (mm) | Foot diameter D (mm) | SW key | Screw length B (mm) | Static load (N) | Foot height G (mm) | Height without washer H (mm) |
|----------------------------------------------|--------------|-----|----------|---------------|----------------------------|----------------------|--------|---------------------|-----------------|--------------------|------------------------------|
| Adjustable foot with foot ø40mm, PA+GF-steel | 13879        | 0   | M12      | 27            | 105                        | 40                   | 12     | 75                  | 10000           | 16,5               | 102                          |
| Adjustable foot with foot ø40mm, PA+GF-steel | 13880        | 1   | M12      | 27            | 130                        | 40                   | 12     | 100                 | 10000           | 16,5               | 127                          |
| Adjustable foot with foot ø40mm, PA+GF-steel | 13881        | 0   | M12      | 27            | 155                        | 40                   | 12     | 125                 | 10000           | 16,5               | 152                          |