

- **Materiál patka:** termoplast se skleněnými vlákny
- **Materiál šroub:** pozinkovaná ocel
- **Barva patky:** černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přibjednat [speciální protiskluzovou podložku](#).

Selected variant

Product name	Adjustable foot with ø83mm foot and holes for anchoring, PA+GF-steel
Product code	14251
Height with washer H1 (mm)	144
Foot height G (mm)	27
Foot diameter D (mm)	83
Hole diameter L (mm)	8,5
Height A (mm)	41
Screw length B (mm)	100
Pitch K (mm)	55
Height without washer H (mm)	141
Thread F	M20
Static load (N)	20000
SW key	17

Variants

Product name	Product code	QTY	Height with washer H1 (mm)	Foot height G (mm)	Foot diameter D (mm)	Hole diameter L (mm)	Height A (mm)	Screw length B (mm)	Pitch K (mm)	Height without washer H (mm)	Thread F	Static load (N)	SW key

Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	28396	4	133	18	83	8,5	30	100	54	130	M16	16000	13
Adjustable foot with ø83mm foot and holes for anchoring, PA+GF-steel	14251	0	144	27	83	8,5	41	100	55	141	M20	20000	17
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13896	0	91	27	83	8,5	38	50	55	88	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13897	0	116	27	83	8,5	38	75	55	113	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13898	0	141	27	83	8,5	38	100	55	138	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13899	0	166	27	83	8,5	38	125	55	163	M16	20000	16

Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13900	0	191	27	83	8,5	38	150	55	188	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13901	0	216	27	83	8,5	38	175	55	213	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13902	0	241	27	83	8,5	38	200	55	238	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	14391	0	119	27	83	8,5	41	75	55	116	M20	20000	17
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	14392	0	169	27	83	8,5	41	125	55	166	M20	20000	17
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-steel	14393	0	194	27	83	8,5	41	150	55	191	M20	20000	17

Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	14394	0	219	27	83	8,5	41	175	55	216	M20	20000	17
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	14395	0	244	27	83	8,5	41	200	55	241	M20	20000	17
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	14396	0	269	27	83	8,5	41	225	55	266	M20	20000	17
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	29226	1	-	20	103	12,5	32	100	73	132	M16	18000	13
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13802	0	91	27	83	8,5	38	50	55	88	M10	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13803	0	116	27	83	8,5	38	75	55	113	M10	15000	14

Adjustable foot with ø83mm foot and holes for anchoring, PA+GF-steel	13804	0	141	27	83	8,5	38	100	55	138	M10	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13805	0	166	27	83	8,5	38	125	55	163	M10	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13806	0	91	27	83	8,5	38	50	55	88	M12	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13807	0	116	27	83	8,5	38	75	55	113	M12	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13808	0	141	27	83	8,5	38	100	55	138	M12	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13809	0	166	27	83	8,5	38	125	55	163	M12	15000	14

Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13810	0	91	27	83	8,5	38	50	55	88	M14	20000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13811	0	116	27	83	8,5	38	75	55	113	M14	20000	14
Nastavitelná noha s pätkou ø83mm a otvory pro kotvení, PA+GF-ocel'	13812	0	141	27	83	8,5	38	100	55	138	M14	20000	14
Threaded sealing plugs Type 1, PA 6, yellow	13813	0	166	27	83	8,5	38	125	55	163	M14	20000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13814	0	191	27	83	8,5	38	150	55	188	M14	20000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13815	0	216	27	83	8,5	38	175	55	213	M14	20000	14