

- **Foot material:** thermoplastic
- **Screw material:** stainless steel
- **Foot color:** black

The static load mentioned is calculated at the center of the screw. These values are lower in the case of vibrations or dynamic loads.

This system is developed for use in dairies, pharmaceutical and food industries, and factories that are subject to the strictest hygiene regulations.

The housing is equipped with a seal that, by its adhesion to the smooth surface of the screw, ensures that dirt does not enter.

USDA ORGANIC Certificate

USDA Organic is an American national form of certification awarded according to criteria for organic agriculture.

The goal of this federal organization is to support trade, agricultural organic production and rural communities, protect the environment and ensure food safety.

Selected variant

Product name	Adjustable foot for clean operations with foot, stainless steel, PA
Product code	14193
Foot diameter D (mm)	123
Thread F	M30
Height H1 (mm)	197
Foot height G (mm)	32
Stroke adjustment (mm)	65
SW key	26
Diameter D1 (mm)	42
Static load (N)	30000
Height B (mm)	150
Height A (mm)	47
Height H2 (mm)	132

Variants

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.cz

E-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.

Product name	Product code	QTY	Foot diameter D (mm)	Thread F	Height H1 (mm)	Foot height G (mm)	Stroke adjustment (mm)	SW key	Diameter D1 (mm)	Static load (N)	Height B (mm)	Height A (mm)	H (mm)
Adjustable foot for clean operation and with foot, stainless steel, PA	14189	0	103	M20	193	30	65	17	30	20000	150	43	1
Adjustable foot for clean operations with foot, stainless steel, PA	14190	0	103	M24	194	30	65	20	35	20000	150	44	1
Nastavitelná noha pro čisté převádzkay s pätkou, nerez, PA	14191	0	123	M20	195	32	65	17	30	30000	150	45	1
Adjustable leg for clean operation with foot, stainless steel, PA	14192	0	123	M24	196	32	65	20	35	30000	150	46	1
Adjustable foot for clean operations with foot, stainless steel, PA	14193	0	123	M30	197	32	65	26	42	30000	150	47	1