

- **Materiál tělo:** nerezová ocel
- **Materiál kulička:** nerezová ocel
- **Barva:** stříbrná

Zvýšená zátěž.

Selected variant

Product name	Spring-loaded ball lock screw, for Allen key, stainless steel, increased strength
Product code	14895
I3	5,5
N2	270
Weight (g)	98
Length L (mm)	48
Thread D	M24
N1	130
Ball diameter D1 (mm)	15
Y (mm)	12

Variants

Product name	Product code	QTY	I3	N2	Weight (g)	Length L (mm)	Thread D	N1	Ball diameter D1 (mm)	Y (mm)
Spring-loaded locking screw with ball, for hex, stainless steel, increased strength	14886	0	0,5	7	0,3	9	M3	5	1,5	1,5
Aretační skrutka s guličkou odpružená, na imbus, nerez, zvětšená síla	14887	0	0,8	22	0,5	10	M4	12	2,5	2
Locking screw with spring-loaded ball, for hex, stainless steel, increased strength	14888	11	0,9	30	1,3	14	M5	19	3	3

Product name	Product code	QTY	I3	N2	Weight (g)	Length L (mm)	Thread D	N1	Ball diameter D1 (mm)	Y (mm)
Sprung ball lock screw, for Allen, stainless steel, increased force	14889	0	1	40	1,8	15	M6	28	3,5	3
Sprung ball lock screw, for Allen key, stainless steel, increased strength	14890	15	1,5	73	3,6	16	M8	47	5	4
Locking screw M10x23mm with ball spring-loaded on hex increased strength stainless steel	14891	0	2	100	6	23	M10	66	6	5
Spring-loaded ball lock screw, Allen key, stainless steel, increased strength	14892	0	2,5	120	13	26	M12	66	8	6
Locking screw with spring-loaded ball, for hex, stainless steel, increased force	14893	0	3,5	180	32	33	M16	90	10	8
Sprung ball lock screw, for hex, stainless steel, increased strength	14894	0	4,5	240	63	43	M20	115	12	10
Spring-loaded ball lock screw, for Allen key, stainless steel, increased strength	14895	0	5,5	270	98	48	M24	130	15	12