

- **Materiál patka:** galvanizovaná ocel + vulkanizovaná guma NBR 80 Shore
- **Materiál šroub:** galvanizovaná ocel C40
- **Barva patky:** stříbrná + černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

Selected variant

Product name	Adjustable leg with vulcanized foot ø60mm, galvanized steel
Product code	14317
Thread F	M10
Foot diameter D (mm)	60
Height A (mm)	32
Foot height G (mm)	22
SW key	14
Height H (mm)	132
Static load (N)	7000
Screw length B (mm)	100

Variants

Product name	Product code	QTY	Thread F	Foot diameter D (mm)	Height A (mm)	Foot height G (mm)	SW key	Height H (mm)	Static load (N)	Screw length B (mm)
Adjustable foot with vulcan. foot ø60mm, galvanised steel	14316	11	M10	60	32	22	14	82	7000	50
Adjustable leg with vulcanized foot ø60mm, galvanized steel	14317	18	M10	60	32	22	14	132	7000	100

Product name	Product code	QTY	Thread F	Foot diameter D (mm)	Height A (mm)	Foot height G (mm)	SW key	Height H (mm)	Static load (N)	Screw length B (mm)
Adjustable foot with vulcanized foot ø60mm, galvanized steel	14318	0	M12	60	32	22	14	82	7000	50
Adjustable leg with vulcan. foot Ø60mm, screw M12x100mm, galvanized. steel	14319	4	M12	60	32	22	14	132	7000	100
Adjustable foot with vulcanized foot ø60mm, galvanized steel	14320	2	M12	60	32	22	14	182	7000	150
Adjustable foot with vulcanized foot ø60mm, galvanized steel	14321	0	M14	60	32	22	14	82	7000	50
Adjustable foot with vulcan. foot ø60mm, galvanized steel	14322	0	M14	60	32	22	14	132	7000	100
Adjustable foot with vulcan. foot ø60mm, galvanized steel	14323	0	M14	60	32	22	14	182	7000	150
Adjustable foot with vulcan. foot ø60mm, galvanized steel	14324	5	M16	60	32	22	16	107	7000	75
Adjustable foot with vulcan. foot ø60mm, galvanized steel	14325	30	M16	60	32	22	16	132	7000	100
Adjustable foot with vulcanized with foot ø60mm, galvanized. steel	14326	6	M16	60	32	22	16	182	7000	150

Product name	Product code	QTY	Thread F	Foot diameter D (mm)	Height A (mm)	Foot height G (mm)	SW key	Height H (mm)	Static load (N)	Screw length B (mm)
Adjustable foot with vulcanized foot ø60mm, galvanised steel	14327	2	M16	60	32	22	16	232	7000	200
Adjustable foot with vulcan. foot ø60mm, galvanized steel	14328	5	M20	60	32	22	20	108	7000	75
Adjustable foot with vulcan. foot ø60mm, galvanized steel	14329	0	M20	60	32	22	20	133	7000	100
Adjustable foot with vulcan. foot ø60mm, galvanized steel	14330	0	M20	60	32	22	20	183	7000	150
Adjustable foot with vulcanized foot ø60mm, galvanized steel	14331	0	M20	60	32	22	20	233	7000	200
Adjustable foot with vulcan. foot ø60mm, galvanized. steel	14332	0	M20	60	32	22	20	283	7000	250