

Frame made of pressed steel - yellow zinc. Swivel head mounted on two ball bearings with plastic dust cover. Wheel axle bolt/nut.

Wheel center made of **cast iron**, **polyurethane** tread (95 Shore A), center mounted on **ball** bearing.

In case the product is not in stock in sufficient quantity, its delivery time can be up to 120 days.

Selected variant

Product name	
Product code	0
Load capacity (kg)	550
Fastening	Deska
Brake	-
Height H (mm)	206
Board size S (mm)	115x140
Diameter D (mm)	150
Hole spacing R (mm)	81x105
Width B (mm)	45

Variants

Product name	Product code	QTY	Load capacity (kg)	Fastening	Brake	Height H (mm)	Board size S (mm)	Diameter D (mm)	Hole spacing R (mm)	Width B (mm)
	27538	0	350	Deska	-	140	115x140	100	81x105	35
	27539	2	350	Deska	+	140	115x140	100	81x105	35
	27541	0	400	Deska	+	170	115x140	125	81x105	40
	27540	0	400	Deska	-	170	115x140	125	81x105	40
	27544	0	900	Deska	-	248	115x140	200	81x105	50
	27543	0	550	Deska	+	206	115x140	150	81x105	45
	27542	0	550	Deska	-	206	115x140	150	81x105	45
	27546	0	350	Pevné	-	140	115x140	100	81x105	35

Product name	Product code	QTY	Load capacity (kg)	Fastening	Brake	Height H (mm)	Board size S (mm)	Diameter D (mm)	Hole spacing R (mm)	Width B (mm)
	27545	0	900	Deska	+	248	115x140	200	81x105	50
	27547	0	400	Pevné	-	170	115x140	125	81x105	40
	27549	0	900	Pevné	-	248	115x140	200	81x105	50
	27548	0	550	Pevné	-	206	115x140	150	81x105	45

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.czE-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.