

- **Material:** thermoplastic with glass fibers
- **Color:** matt black

Self-extinguishing material certified UL94 V 0 with **resistance up to 150°C**.

Easy installation by inserting a screw with a head from above into a through hole with a recess for the screw.

Selected variant

Product name	Bridge handle with hole PA+GF UL94-V0
Product code	0
Height H (mm)	9
G.	6
Length A (mm)	139
Height F (mm)	41
Diameter D (mm)	13
Width E (mm)	26
Diameter d (mm)	8,5
Pitch B (mm)	117

Variants

Product name	Product code	QTY	Height H (mm)	G.	Length A (mm)	Height F (mm)	Diameter D (mm)	Width E (mm)	Diameter d (mm)	Pitch B (mm)
Bridge handle with hole PA+GF UL94-V0	12564	0	7	6	112	36	10,5	21	6,5	93,5
Bridge handle with hole PA+GF UL94-V0	12565	2	9	6	139	41	10,5	26	6,5	117
Bridge handle with hole PA+GF UL94-V0	12566	3	9	6	139	41	13	26	8,5	117

A components s.r.o.

Bohunická 493/81
619 00 Brno

Web: www.acomponents.cz

E-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.

Product name	Product code	QTY	Height H (mm)	G.	Length A (mm)	Height F (mm)	Diameter D (mm)	Width E (mm)	Diameter d (mm)	Pitch B (mm)
Bridge handle with hole PA+GF UL94-V0	12567	0	7	9	156	45	10,5	27	6,5	132
Handle bridge with hole PA+GF UL94-V0	12568	0	9	7	156	45	13	27	8,5	132
Bridge handle with hole PA+GF UL94-V0	12569	0	9	8	204	50	13	28	8,5	179