

Spiral suitable for protecting hydraulic pipes and their distributions, where a high degree of self-extinguishing and fire resistance is required.

Resists abrasion, impact, UV radiation, oil, ozone and flame.

- **Material:** HDPE derivative
- **Temperature range of use:** -30°C - +110°C
- **Density:** 1.05 g/ml
- **Shore D hardness:** 68
- **Melt volume rate** (230°C/2.16 kg): 10 min 1 MVR
- **VICAT softening point** (50N): 75°C
- **Tensile strength at slip:** -1/-2 Mpa 18
- **Elongation at break:** -1/-2>100%
- **Fire resistance:** UL 94.V0

Selected variant

Product name	Ochranné špirály FR - Extra
Product code	0
Climb P	29-31
Outer diameter D (mm)	50
ID inside diameter (mm)	43
Weight/1m (kg)	0,520
Wall thickness T (mm)	3,3

Variants

Product name	Product code	QTY	Climb P	Outer diameter D (mm)	ID inside diameter (mm)	Weight/1m (kg)	Wall thickness T (mm)
Protective spirals FR - Extra	30592	0	12-14	16	13	0,080	2
FR - Extra protective spirals	30594	0	20-21	25	20	0,140	2,5
Protective spirals FR - Extra	30593	0	0,077	20	16	0,115	2
Protective spirals FR - Extra	30595	0	22-23	32	27	0,260	2,7

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.cz

E-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.

Product name	Product code	QTY	Climb P	Outer diameter D (mm)	ID inside diameter (mm)	Weight/1m (kg)	Wall thickness T (mm)
Protective spirals FR - Extra	30596	0	25-26	40	34	0,300	3
Ochranné špirály FR - Extra	30597	0	29-31	50	43	0,520	3,3

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.czE-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.