

The USIT ring with a centering lip USS is a top-notch sealing element designed for maximum reliability and durability. This special ring combines the advantages of the traditional USIT ring with the addition of a vulcanized centering lip, which ensures precise positioning and minimizes the risk of leakage.

When tightening the screw connection (joint), the sealing lip rests on the opposing surfaces, which are thus sealed by it. Made of high-quality materials, it is resistant to high pressures and temperatures, which makes it ideal for demanding industrial applications. Thanks to its design, it is easy to install and provides long-term protection against wear.

- **Material:** steel/NBR

Selected variant

Product name	USIT rings, USS
Product code	0
Material	ocel / NBR
Thread	M8
t.	1
d.	8,7
Diameter D (mm)	13

Variants

Product name	Product code	QTY	Material	Thread	t.	d.	Diameter D (mm)
USIT rings, USS	30551	7869	ocel / NBR	1/4"	2,03	13,74	20,57
USIT rings, USS	30562	1200	ocel / NBR	M8	1	8,7	13
USIT rings, USS	30564	1350	ocel / NBR	M24	2	24,7	32
USIT rings, USS	30563	1194	ocel / NBR	M20	1,5	20,7	28
USIT rings, USS	30568	613	ocel / NBR	2"	3,2	60,58	73,03
USIT rings, USS	30554	2070	ocel / NBR	1"	2,5	33,89	42,8
USIT rings, USS	30555	1755	ocel / NBR	M16	1,5	16,7	24
USIT rings, USS	30552	6229	ocel / NBR	3/4"	2,5	27,05	34,93
USIT rings, USS	30561	895	ocel / NBR	1 1/4"	2,5	42,93	52,38
USIT rings, USS	30569	578	ocel / NBR	5/8"	2,5	23,49	31,75
USIT rings, USS	30549	4400	ocel / NBR	3/8"	2,03	17,28	23,8

Product name	Product code	QTY	Material	Thread	t.	d.	Diameter D (mm)
USIT rings, USS	30550	4130	ocel / NBR	1/2"	2,5	21,54	28,58
USIT rings, USS	30557	1950	ocel / NBR	M22	2	22,7	30
USIT rings, USS	30558	1020	ocel / NBR	M18	1,5	18,7	26
USIT rings, USS	30565	1059	ocel / NBR	M26	2	26,7	35
USIT rings, USS	30567	585	ocel / NBR	1 1/2"	2,5	48,44	58,6
USIT rings, USS	30553	3335	ocel / NBR	1/8"	2,03	10,37	15,88
USIT rings, USS	30556	4330	ocel / NBR	M14	1,5	14,7	22
USIT rings, USS	30560	1250	ocel / NBR	M10	2,0	10,35	15,88
USIT rings, USS	30559	1282	ocel / NBR	M12	1,5	12,7	18
USIT rings, USS	30570	409	ocel / NBR	M6	1	6,7	10
USIT rings, USS	30566	593	ocel / NBR	M30	2	31	39