

Silent blocks are standardly made of NR/SBR rubber with a hardness of 70 ±5 Shore.

Working temperature range from -20°C to 80°C.

These silent blocks are intended for compressive loads (axial downward load). They are not intended for tensile or shear loads (axially upwards or radially upwards).

In case the product is not in stock in sufficient quantity, its delivery time can be up to 120 days.

Selected variant

Product name	
Product code	26975
Diameter d (mm)	M16
Diameter D (mm)	125
Length L (mm)	40
Thread depth H (mm)	16

Variants

Product name	Product code	QTY	Diameter d (mm)	Diameter D (mm)	Length L (mm)	Thread depth H (mm)
Silent block thread-thread, Type 3	26962	0	M12	75	25	12
Silent block thread-thread, Type 3	26967	0	M12	75	55	12
Thread-to-thread silent block, Type 3	26966	10	M12	75	50	12
Silentblok závit-závit, Typ 3	26968	10	M12	75	70	12
Silent block thread-thread, Type 3	26969	0	M16	100	30	16
Silent block thread-thread, Type 3	26970	10	M16	100	40	16
Silent block thread-thread, Type 3	26972	0	M16	100	55	16

Product name	Product code	QTY	Diameter d (mm)	Diameter D (mm)	Length L (mm)	Thread depth H (mm)
Silent block thread-thread, Type 3	26974	0	M16	100	75	16
Silent block thread-thread, Type 3	26973	9	M16	100	60	16
Silent block thread-thread, Type 3	26971	10	M16	100	50	16
	26977	0	M20	150	50	16
	26976	0	M20	150	45	16
	26975	0	M16	125	40	16
	26921	0	M4	15	15	4
	26978	0	M20	150	55	16
	26979	0	M20	150	60	16
	26923	0	M6	20	15	6
	26925	0	M6	20	25	6
	26927	0	M6	25	10	6
	26929	0	M6	25	17	6
	26931	0	M6	25	23	6
	26936	0	M8	30	28	8
	26942	0	M8	40	27	8
	26943	0	M8	40	28	8
	26955	0	M12	60	25	12
	26965	0	M12	75	45	12
Silent block thread-thread, Type 3	26922	10	M4	15	20	4
Silent block thread-thread, Type 3	26924	8	M6	20	20	6
Silent block thread-thread, Type 3	26926	9	M6	20	30	6
Silent block thread-thread, Type 3	26928	10	M6	25	15	6

Product name	Product code	QTY	Diameter d (mm)	Diameter D (mm)	Length L (mm)	Thread depth H (mm)
Silent block thread-thread, Type 3	26930	10	M6	25	20	6
Silent block thread-thread, Type 3	26932	0	M6	25	25	6
Silent block thread-thread, Type 3	26934	5	M8	30	20	8
Silent block thread-thread, Type 3	26933	10	M6	25	30	6
Thread-to-thread silent block, Type 3	26935	0	M8	30	25	8
Silent block thread-thread, Type 3	26938	8	M8	30	40	8
Hose clamp Double Robust W1 Power Clamp 65-75	26937	7	M8	30	30	8
Silent block thread-thread, Type 3	26940	5	M8	40	20	8
Silent block thread-thread, Type 3	26941	0	M8	40	25	8
Silent block thread-thread, Type 3	26939	0	M8	35	35	8
Silent block thread-thread, Type 3	26944	8	M8	40	30	8
Silent block thread-thread, Type 3	26945	5	M8	40	40	8
Silent block thread-thread, Type 3	26946	0	M8	45	25	8
Thread-to-thread silent block, Type 3	26947	0	M8	45	35	10
Silent block thread-thread, Type 3	26948	0	M10	50	25	10
Silent block thread-thread, Type 3	26951	6	M10	50	40	10
Silent block thread-thread, Type 3	26950	0	M10	50	35	10

Product name	Product code	QTY	Diameter d (mm)	Diameter D (mm)	Length L (mm)	Thread depth H (mm)
Silent block thread-thread, Type 3	26949	1	M10	50	30	10
Silent block thread-thread, Type 3	26952	0	M10	50	42	10
Silent block thread-thread, Type 3	26954	5	M10	50	50	10
Silent block thread-thread, Type 3	26953	0	M10	50	45	10
Silentblok závit-závit, Typ 3	26957	0	M12	60	35	12
Silent block thread-thread, Type 3	26956	8	M12	60	30	12
Silent block thread-thread, Type 3	26959	0	M12	70	35	12
Silent block thread-thread, Type 3	26958	9	M12	60	40	12
Silent block thread-thread, Type 3	26960	10	M12	70	40	12
Silent block thread-thread, Type 3	26963	10	M12	75	30	12
Silent block thread-thread, Type 3	26961	0	M12	70	45	12
Silent block thread-thread, Type 3	26964	10	M12	75	40	12

A components s.r.o.

Bohunická 493/81

619 00 Brno

 Web: www.acomponents.cz

 E-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.